

C3 SERIES

BUILT-IN TEMPERATURE AND HUMIDITY RECORDER

WS-TH20C3

Product Overview:

Wason C3 series is a single model precision instrument for automatic data storage with large screen display. The instrument adopts low-power-consumption design, long standby time; adaptable to many sensors, wide detection range. External sound and light alarm can be connected to achieve high decibel sound and light alarm. C-mi software can be used to achieve parameter setting, data download, data analysis, data export and other functions, and can directly copy data in CSV files from the logger without using C-mi software. Widely used in food, pharmacy, clinical experiments, chemical electronics, archives, agricultural research and other fields.

Product Characteristics:

- 1) USB communication;
- 2) Large screen display;
- 3) Real-time clock;
- 4) °C/°F can be switched;
- 5) Large capacity for data storage;
- 6) Screen query for maximum and minimum values.




Product Parameter:

Sensor type	Temperature and humidity (built-in)
Number of sensors	Dual channel (Temperature and humidity integrated)
Temperature range	-20°C~70°C
Temperature accuracy	± (0.3~0.5) °C
Humidity range	0%RH~100%RH
Humidity accuracy	± (3~5) %RH
Display resolution	Temperature: 0.1°C/0.1°F Humidity: 0.1%RH
Memory resolution	Temperature: 0.1°C/0.1°F Humidity: 0.1%RH
Recording capacity	60000 groups
Record interval	The minimum interval is 1s, can be set in seconds, minutes, and hours
Parameter configuration	Special software configuration
Numerical query	Screen query for maximum and minimum values
Out-of-limit alarm	Internal power supply: buzzer alarm; External power supply: external sound and light alarm, flash warning, internal buzzer alarm

Clock	Real-time clock display
Starting mode	Manual start, the software starts periodically
Stop mode	Manual stop, full stop
Communication interface	USB Type-C
Power supply	High energy lithium battery, DC 5V/1A adapter (optional)
Battery life	2 years valid (default setting)
Host operating environment	-20℃~70℃
Overall dimension	113mm×102mm×32mm
weight	174g
Calibrate	Standard product with factory calibration certificate, CNAS calibration certificate for optional
Shell material	ABS (Shock-resistant)
Keep under warranty	12 months
Product certification	CE certification

Product Accessories:

Accessories			
Name	Power adapter	Type-C Data cable	Calibration certificate
Type	P134	P158	/
Note information	5V/1A (Optional)	/	/
Accessories			
Name	Software Get Business Card	User manual	CNAS Calibration Certificate
Type	/	/	/
Note information	C-mi	(including manual, warranty card, certificate)	Optional


Accessories			
Name	Screwdriver	Audible and Visual Alarm	Lithium Battery
Type	/	P141	P702
Note information	/	AC3 Specific	3.6V Lithium battery
Accessories			
Name	Wall mounting kit		
Type	P111		

Usage Method:

Method 1:

None-drive usage (no special software required, easier to use.)

- ① Stop recording, connect the computer with a USB cable to download data.
- ② Copy data files in CSV format directly from the recorder, which can be opened by text processing software such as EXCEL or TXT.





Method 2:


When you have more requirements for data analysis, please use the dedicated software to download the data, through the dedicated software you can view data reports, data curves, data statistics, record remarks and other information, but also output in PDF files.

- ① Copy the special software to the computer. It's a green software, no need to install, open to use.
- ② Connect the recorder to the computer and set parameters when the recording is stopped.
- ③ Exit the recorder from the computer, placed in the environment that needs to be detected, and turn it on.
- ④ Stop recording, connect the recorder to the computer, view historical data, historical curves,


data statistics, etc., and print data, output PDF and other format files.



Data Reports And Data Curves



Data Reports And Statistics



Output PDF Curve

Output PDF Report

Product Application:

It's widely used in different industries, such as food, pharmacy, electronics, chemicals, transportation, agricultural research, textiles, meteorological & environmental protection, HVAC refrigeration, archives management, and biochemical laboratory, etc.